



FP ATS-9800



FP ATS-8000



FP ATS-9600



FP ATS-8900



FP ATS-9900



FP ATS-309

TABBING/LABELING SYSTEMS

USPS® COMPLIANT

TABBING/LABELING

Automate your mailing operations with time-saving labeling, tabbing, and stamping technology. FP's complete selection of tabbing, labeling, and stamping systems ensures you'll find the right machine for your business, so you save time and money. And, with these mail sealing systems, you can take advantage of Shape-Based Pricing postal discounts while applying labels and tabs to your mail pieces with ease and efficiency. Every model boasts three critical "must-haves" in mail sealing systems: incredible speed, versatility to accommodate a range of materials, and durability and toughness for long-life operation.

FP ATS-8000

The fixed-speed, single tabber gives you all the advantages and cost savings of high-speed tabbing in one compact and economical unit. Every tab – paper, translucent, or clear – is a tight, secure seal, which helps to meet USPS® requirements. Its exceptionally large 17.0" material width capacity is unmatched in the industry.

system specifications	ATS-8000
Speed	12,000 pieces/hr. (8.5" tri-folds)
Media size	3.0" to 17.0" (L) x 5.0" to 11.0" (W)
Media thickness	up to 5/32"
Tab size	1 1/4" to 1 1/2" (standard tabs)
Reel capacity	up to 10.0" diameter (3.0" core)
Dimensions	25.0" (W) x 15.5" (D) x 22.0" (H)
Weight	40 lbs.
Electrical cycle	120 VAC 50/60 Hz
Duty cycle	30 million pieces or 500k pieces/month



SPECIAL FEATURES

- ▶ Tab sensitivity control adjusts for density in tab/wafer seals
- ▶ Accepts rolls of up to 5,000 tabs
- ▶ Feeder utilizes integrated bottom feed for continuous operation
- ▶ Optional CD-860 conveyor stacker and drop tray

FP ATS-309

Whether it's side-to-side or single tabbing, the ATS-309 tabbing machine will make your job more productive and efficient with speeds up to 25,000 pieces per hour. It also meets the newest postal regulations to ensure accuracy every time.

system specifications	ATS-309
Speed	tabbing: up to 25,000 pcs. per hour
	side-to-side: up to 15,000 pcs. per hour
	stamping: up to 20,000 pcs. per hour
Media size	3.5" (W) x 5.0" (L) to 11.0" (W) x 15.0" (L)
Media thickness	up to 1/4"
Number of tabs	1, 2, or 3
Tab accuracy	+/- 1/16"
Reel capacity	two reels, 10" diameter each
Dimensions	28" (W) x 26" (H) x 34" (L)
Weight	97 lbs.
Electrical	110VAC 60Hz/2A



SPECIAL FEATURES

- ▶ Speeds up to 25,000 pcs./hour placing accurate and tightly closed tabs
- ▶ Applies tabs on 2 sides of the mailpiece in a single pass
- ▶ Applies USPS® sensitive roll stamps
- ▶ Apply 1.5" tabs side-to-side or top-to-side

TABBING/LABELING SYSTEMS

FP ATS-9800

Apply one or two tabs with this pin-feed, dual tabber and get more done in less time! This versatile and affordable model offers double-tab throughput speeds of up to 22,000 pieces per hour on tri-folded mailers. The built-in feeder runs a wide variety of materials up to 1/8" thick and has a detachable hopper so it can be used in-line.

system specifications

AJ-9800

Speed	up to 22,000 pieces per hr.
Media size	5.5" (W) x 3.5" (L) to 12.0" (W) x 9.0" (L)
Media thickness	up to 1/8"
Tab size	13/16" (W) x 13/16" (L) to 15/16" (L)
Reel capacity	25,000 tab box
Tab accuracy	+/- 1/16"
Hopper capacity	300 tri-folded mailers
Dimensions	10.5" (W) x 15.0" (H) x 19.0" (L)
Weight	40 lbs.
Electrical	110 VAC 60Hz/1A (optional 220 VAC 50 Hz/1A)
Duty cycle	30 million pieces total or 50,000 pcs./mo.



SPECIAL FEATURES

- ▶ Built-in friction feeder holds up to 300 mailers
- ▶ Detachable hopper enables in-line use
- ▶ Complies with USPS® bulk mail regulations for folded mailers
- ▶ Optional CD-860 conveyor-stacker and drop tray

FP ATS-8900

This multiple tabber/stamp affixer is the only machine available in its price range that tabs 1 to 3 tabs or stamps in-line. Capable of handling medium range production consistently, reliably, and quickly, it works at speeds of up to 25,000 pieces per hour placing accurate and tight closed tabs. Friendly firmware enables easy setup and smooth operation.

system specifications

ATS-8900

Speed	tabbing up to 25,000 pcs./hr. (1 tab)
	up to 15,000 pcs./hr. (2 tabs)
	up to 10,000 pcs./hr. (3 tabs)
Reel capacity	calculated with tri-fold 8 1/2" x 11"
Stamping	up to 8,000 pcs./hr. (#10s)
Media size	minimum 5.0" (W) x 3.0" (L)
	maximum 17.0" (W) x 13.0" (L)
	detachable feeder 17.0" (W) x 12.0" (L)
Media thickness	up to 3/8"
Tab size	3/4" to 1 1/2"
Production rates	16.0" diameter, 20,000 1" diameter tabs
Tab accuracy	+/- 1/16"
Dimensions	25.0" (W) x 27.0" (H) x 41.0" (L)
Weight	70 lbs.
Electrical	110 VAC 60Hz/2A



SPECIAL FEATURES

- ▶ Innovative side tabbing enables greater consistency
- ▶ Places up to 3 tabs per piece according to USPS® regulations
- ▶ In-line or built-in feeder for stand alone applications
- ▶ Optional CD-860 conveyor stacker and drop tray
- ▶ Optional FF-20 friction feeder

FP ATS-9900 & FP ATS-9950

Fast and versatile, these top-of-the-line, high-end tabletop labelers/tabbers handle up to 35,000 pcs./hr. and up to three tabs in one pass. They apply clear, translucent, or paper tabs with ease in a variety of tab sizes and can apply up to 4" wide. An innovative side tab application allows maximum productivity – simply load large tab rolls and jobs keep running.

system specifications	ATS-9900/ATS-9950
Speed	single tab: up to 35,000 pcs./hr. double tab: up to 30,000 pcs./hr. triple tab: up to 25,000 pcs./hr.
Material size	5.0" (W) x 3.0" (L) to 17.0" (W) x 13.0" (L)
Material thickness	up to 1/2"
Tab size	minimum 3/4" (W) x 3/4" (L) maximum 2" (W) x 2" (L)
Labels	up to 4" wide backing paper w/ supplied wide applicator head
Roll size	up to 19.5" diameter (3" core)
Number of tabs	1, 2, or 3
Tab accuracy	+/- 1/16"
Dimensions	27" (W) x 33" (D) x 29" (H) - FP ATS-9900 27" (W) x 33" (D) x 71" (H) - FP ATS-9950
Weight	200 lbs.
Electrical	115VAC 50/60 Hz
Duty cycle	120 million total or 2 million pcs./mo.



SPECIAL FEATURES

- ▶ Production speeds of up to 35,000 pcs./hr.; double tab at 30,000 pcs./hr.
- ▶ Applies tabs, labels, or USPS® stamps one, two, or three at a time
- ▶ Available in a console model (FP ATS-9950)
- ▶ Optional CD-860 conveyor-stacker and drop tray

FP ATS-9600 & FP ATS-9700

Unlike most tabbers in their class that can only output paper tabs, the fast and versatile FP ATS-9600 high-speed labeler/tabber and FP ATS-9700 labeler/tabber/stamper affixer handle up to 25,000 pieces an hour on a typical tri-fold mailer.

system specifications	ATS-9600/ATS-9700
Speed	tabbing up to 25,000 pcs./hr. (tri-folds) labeling up to 25,000 pcs./hr. (#10) stamping up to 8,000 pcs./hr. (#10)
Media size	minimum 3 5/8" (W) x 5.0" (L) maximum 16.0" (W) x 18.0" (L)
Media thickness	up to 5/16" (up to 1/8" for tabbing)
Tab size	+/- 1/16"
Hopper capacity	250 #10 envelopes
Dimensions	16.5" (W) x 19.0" (H) x 18.0" (L)
Weight	70 lbs.
Electrical	110 VAC 60 Hz/2A
Duty cycle	30 million total or 500,000 pcs./mo.



SPECIAL FEATURES

- ▶ Top-load, friction bottom feeder for continuous operation
- ▶ Optional CD-860 conveyor stacker and drop tray
- ▶ Tab/label media sensor adjusts to various types of materials
- ▶ Cantilevered head allows unit to run wider materials

